

The **ERGIT** series

**TRH**



## 9400

<b>Chassis</b>	ACTIO™ – Full chassis with oscillation - Front steering - 4 equal wheel drive - RGS™ Reversibility					
<b>Engine type</b>	Direct injection diesel					
<b>N. Cylinders</b>	4 Turbo					
<b>Output kW/HP ECE R24</b>	61/83					
<b>Maximum rpm</b>	2600					
<b>Cooling</b>	Water					
<b>Tank Capacity (litres/gal)</b>	60/16					
<b>Transmission</b>	Hydromechanical – Continual variation of forward speeds in both drive direction from 0>40 Km/h with a mechanical selector of the 4 speed variator – “Automotive” device					
<b>PTO</b>	Indep. and synchronised at 540/540E rpm with progressive electrohydr. engagement					
<b>Hydraulic power lift</b>	Position and draft control with 3 point hitch with joy-stick					
<b>Capacity (N/Kg-N/lbs)</b>	20580/2100 - 20580/4630					
<b>Brakes</b>	Service brakes: on 4 wheels disk brakes in oil bath with hydraulic engagement					
	Steering brakes - Emergency and parking: band type on transmission					
<b>Tyres</b>	12.4 R20	11.5/80-15.3	320/65R18	11LR16	300/70R20	400/55-17.5
<b>Min. Outer Width (mm/in)</b>	1520/59.8	1430/56.3	1460/57.5	1420/55.9	1420/55.9	1690
<b>Ground Clearance (mm/in)</b>	275/10.8	275/10.8	275/10.8	275/10.8	310/12.2	265
<b>Weight with safety bar (Kg/lbs)</b>	1940-2040/4280-4500					
<b>With cab (Kg/lbs)</b>	2090-2190/4610-4830					
<b>Dimensions: wheel base (mm/in)</b>	1595/62.8					
<b>Lenght (mm/in)</b>	3410/134					
<b>Height: with roll bar (mm/in)</b>	2310/90.9					
<b>With cab (mm/in)</b>	2250/88.6					